

Product Data Sheet

Model identifier(s):	HL 3762				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only	
Nominal heat output	P_{nom}	2,0	kW	manual heat charge control, with integrated thermostat	N.A.
Minimum heat output (indicative)	P_{min}	1,0	kW	manual heat charge control with room and / or outdoor temperature feedback	N.A.
Maximum continuous heat output	$P_{max,c}$	2,0	kW	electronic heat charge control with room and / or outdoor temperature feedback	N.A.
Auxiliary electricity consumption				fan assisted heat output	N.A.
At nominal heat output	el_{max}	0,000	kW	Type of heat output / room temperature control	
At minimum heat output	el_{min}	0,000	kW	single stage heat output and no room temperature control	no
In standby mode	el_{SB}	0,000	W	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	yes
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	no
				Other control options	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	no
				with distance control option	no
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Clatronic International GmbH, Industriering Ost 40, 47906 Kempen Germany				
N.A. = not applicable					